

GHGT, Melbourne, 22.10.2018

## Retrofitability of CO<sub>2</sub> capture technologies to cement plants



Mari Voldsund (SINTEF), Helmut Hoppe (VDZ), Johannes Ruppert (VDZ), Daniel Sutter (ETH), David Berstad (SINTEF), Matteo Romano (Politecnico di Milano), Giovanni Cinti (Italcementi)



# Introduction



---

- H2020 project CEMCAP
- Motivation:
  - 7-9% of global anthropogenic CO<sub>2</sub> emissions from the cement industry – CCS only viable option
  - Cement plants lifetime: ca 30-50 year  
→ Retrofitability important



# CEMCAP technologies

- MEA (reference)
- Oxyfuel process
- Chilled ammonia process (CAP)
- Membrane-assisted CO<sub>2</sub> liquefaction (MAL)
- Calcium looping (CaL)
  - Tail-end
  - Integrated entrained flow



# Approach


---

What would a plant owner have to consider?

- Impact on cement production
- Equipment and footprint
- Utilities and services
- New chemicals/subsystems
- Available experience

Color coding:


✓	retrofitability o.k
!	<i>some</i> attention needed for plant retrofit
!!	special attention needed for plant retrofit
?	needs further assessment for plant retrofit
X	retrofit not possible



# Impact on cement production

	Criteria	MEA/ amine	Oxyfuel	CAP	MAL	CaL (tail- end)	CaL (integr ated)
1	Impact on cement production	✓	!!	✓	✓	✓	!
2	Equipment and footprint						
3	Utilities and services						
4	Introduction of new chemicals/subsystems						
5	Available experiences						


- Post combustion – no impact
- Oxyfuel – impact on clinker cooler, kiln, calciner, preheater...
- CaL integrated – impact on calciner and preheater



# Equipment and footprint

	Criteria	MEA/ amine	Oxyfuel	CAP	MAL	CaL (tail- end)	CaL (integr- ated)
1	Impact on cement production	✓	!!	✓	✓	✓	!
2	Equipment and footprint	!	!!	!	!	!	!!
3	Utilities and services						
4	Introduction of new chemicals/subsystems						
5	Available experiences						


- *Some* attention needed for all technologies
- Post combustion – can be installed away from kiln
- Oxyfuel and CaL integrated – space required close to kiln



# Utilities and services

	Criteria	MEA/ amine	Oxyfuel	CAP	MAL	CaL (tail- end)	CaL (integr ated)
1	Impact on cement production	✓	!!	✓	✓	✓	!
2	Equipment and footprint	!	!!	!	!	!	!!
3	Utilities and services	!	!	!	!	!	!
4	Introduction of new chemicals/subsystems						
5	Available experiences						


- Amine and CAP: Steam and power
- Oxyfuel and MAL: Power demand
- CaL: Coal demand, integrated power generation (import/export)



# New chemicals/subsystems

	Criteria	MEA/ amine	Oxyfuel	CAP	MAL	CaL (tail- end)	CaL (integr- ated)
1	Impact on cement production	✓	!!	✓	✓	✓	!
2	Equipment and footprint	!	!!	!	!	!	!!
3	Utilities and services	!	!	!	!	!	!
4	Introduction of new chemicals/subsystems	!	!	!	✓	!	!
5	Available experiences						

- MEA: amine
- Oxyfuel: ASU, possibly ORC
- CAP: ammonia, refrigeration
- MAL: refrigeration
- CaL: ASU, steam cycle





# Available experiences (I)


	Criteria	MEA/ amine	Oxyfuel	CAP	MAL	CaL (tail- end)	CaL (integr- ated)
1	Impact on cement production	✓	!!	✓	✓	✓	!
2	Equipment and footprint	!	!!	!	!	!	!!
3	Utilities and services	!	!	!	!	!	!
4	Introduction of new chemicals/subsystems	!	!	!	✓	!	!
5	Available experiences	✓	?	!			

Amine:  
Boundary dam  
Norcem Brevik  
370 ton CO<sub>2</sub> / 2700 h



Oxyfuel:  
CEMCAP – unit pilots


CAP:  
Mountaineer  
50 MW<sub>th</sub>  
CEMCAP



# Available experiences (II)



	Criteria	MEA/ amine	Oxyfuel	CAP	MAL	CaL (tail- end)	CaL (integr- ated)
1	Impact on cement production	✓	!!	✓	✓	✓	!
2	Equipment and footprint	!	!!	!	!	!	!!
3	Utilities and services	!	!	!	!	!	!
4	Introduction of new chemicals/subsystems	!	!	!	✓	!	!
5	Available experiences	✓	?	!	?	!	?

MAL:  
CEMCAP liquefaction  
pilot  
Norcem membrane  
testing





CaL tail-end:  
La Pereda 1.7 MW  
CEMCAP

CaL integrated:  
CEMCAP  
Laboratory scale



# Retrofitability versus cost

	Criteria	MEA/ amine	Oxyfuel	CAP	MAL	CaL (tail- end)	CaL (integr- ated)
1	Impact on cement production	✓	!!	✓	✓	✓	!
2	Equipment and footprint	!	!!	!	!	!	!!
3	Utilities and services	!	!	!	!	!	!
4	Introduction of new chemicals/subsystems	!	!	!	✓	!	!
5	Available experiences	✓	?	!	?	!	?



# Conclusions


	Criteria	MEA/ amine	Oxyfuel	CAP	MAL	CaL (tail- end)	CaL (integr- ated)
1	Impact on cement production	✓	!!	✓	✓	✓	!
2	Equipment and footprint	!	!!	!	!	!	!!
3	Utilities and services	!	!	!	!	!	!
4	Introduction of new chemicals/subsystems	!	!	!	✓	!	!
5	Available experiences	✓	?	!	?	!	?

- Most aspects require *some* attention
- *No* aspects assessed as *retrofit not possible* for any technologies
- Post-combustion technologies easier retrofit

Full report:

D4.5 Retrofitability study for CO<sub>2</sub> capture technologies in cement plants

To be shared in: <https://zenodo.org/communities/cemcap/>



# CEMCAP Partners

## Cement Producers



**HEIDELBERGCEMENT**

## Technology providers



## R&D providers




**ETH** zürich



**vdz.**

Coordinated by SINTEF



## Acknowledgements

This project has received funding from the European Union's Horizon 2020 research and innovation programme under grant agreement no 641185

This work was supported by the Swiss State Secretariat for Education, Research and Innovation (SERI) under contract number 15.0160

[www.sintef.no/cemcap](http://www.sintef.no/cemcap)

Twitter: @CEMCAP\_CO2

